



// ONE BRAND // ONE SOURCE // ONE SYSTEM

REMALINE 60 - The lining for protection from impact wear

REMA TIP TOP's high-quality **REMALINE** lining offers optimum surface protection for your machinery and equipment while minimizing production downtime, reducing maintenance costs, and increasing productivity.

APPLICATION AREAS

Due to high abrasion resistance, **REMALINE 60** excels at protecting against impact and dry wear. **REMALINE 60** is commonly used in coal handling and other dry, bulk material applications. **REMALINE 60** can be vulcanized to non-driven pulleys to increase the friction coefficient and improve conveyor performance.

TYPICAL FIELDS OF USE

- Lining for vibration feeders, slides, bunkers, chutes and sieve tubs
- Coating of idlers and constriction and bend pulleys for medium to high belt tension

ADVANTAGES

- Protection against impact wear abrasion caused by dry, sharp-edged material
- Easy and fast installation
- Increases the life of your equipment
- Technical consultation and data available anytime



Hopper lined with REMALINE 60

TECHNICAL PROPERTIES

Product Characteristics	REMALINE 60 is a mixture of styrene, butadiene and isoprene rubber with good wear resistance against dry wear and impact.	
	CN bonding layer: REMALINE 60 comes equipped with a CN bonding layer, which affords the product an extremely good adhesive quality in combination with the REMA TIP TOP adhesive systems.	
Storage Stability	Max. 24 months At 77°F ± 3.6°F with no loss in quality Subject to DIN regulation 7716	
Color		Black
Polymer	DIN ISO 1629	BR/IR/SBR
Hardness	DIN ISO 7619-1	60 Shore A
Abrasion	DIN ISO 4649	90 mm ³
Specific Weight	DIN EN ISO 1183-1	1.13 g/cm ³ (70.54 lb/ft ³)
Tensile Strength	DIN 53 504	18 N/mm ²
Elongation at break	DIN 53 504	470%
Resilience Elasticity	DIN 53 512	44%
Tear Growth Resistance	ISO 34-1 Method A	15 N/mm
Available sizes*	Standard thickness	1/8", 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", 3/4", 1", 1-1/8", 1-5/8", 2"
	Standard width	5', 6½'

*Other sizes available on request. REMALINE 60 is also available with fabric reinforcement.

REMA TIP TOP/North America, Inc.

1500 Industrial Blvd. • Madison, GA 30650 • Phone 800.334.REMA (7362) • 706.752.4000 • Fax 706.752.4015 → www.rematiptop.com